Configurations & accessories

Models in detail

✓ Standard
o Option
x Unavailable
* Retrofittable

Models in detail	CT	CTS	CTM	CTM RL	CTMplus	CTM P	CTM P RL	CTM F	CTM F RL	CTM PF	CTM PF RL	TwinTower CTM + CTM RL
Electrical connection 380–415 V | 50–60 Hz | 16 amp | 3-phase	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Output 5800–7100 W	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dimensions (W/D/H) Coffee machine without refrigerator Coffee machine with refrigerator	320x600x646 mm	412x600x646 mm	320x600x646 mm 600x600x646 mm	692x600x646 mm	412x600x646 mm 692x600x646 mm	488x600x646 mm 768x600x646 mm	580x600x646 mm 860x600x646 mm	920x600x646 mm
Manually adjustable machine output 85–172 mm	✓	✓	✓	✓	✓	✓	✓	✓
Weight	53kg	67kg	58/85kg	86kg	67/92 kg	69/92 kg	84/100 kg	143 kg
Standard								
1 grinder	✓	✓	✓	✓	✓	✓	✓	✓
57 mm feet	✓	✓	✓	✓	✓	✓	✓	✓
Bean hopper ~1.7 kg	✓	✓	✓	✓	✓	✓	✓	✓
Cold milk/cold milk foam*	x	✓	✓	✓	✓	✓	✓	✓
Foot skirting 57 mm	o	o	o	✓	o	o	o	o
ISQ (Intelligent Shot Quality)	✓	✓	✓	✓	✓	✓	✓	✓
Mains water supply	✓	✓	✓	✓	✓	✓	✓	✓
Outer material: Alunox	✓	✓	✓	✓	✓	✓	✓	✓
Powder unit 2 kg	x	x	x	x	✓	x	✓	x
Syrup flavours 1–4	x	x	x	x	x	x	✓	o
Volume 70 dB	✓	✓	✓	✓	✓	✓	✓	✓
Optionen								
2 milk varieties	x	o	o	o	o	o	o	o
2 grinders	x	o	o	o	o	o	o	o
77 mm feet	o	o	o	o	o	o	o	o
Automatic machine output 96–192 mm	o	o	o	o	o	o	o	o
Bean detection	o	o	o	o	o	o	o	o
Electrical connection 220–240 V | 50–60 Hz | 32 amp | 1-phase 220–240 V | 50–60 Hz | 16 amp | 1-phase* 220–240 V | 50–60 Hz | 13 amp | 1-phase *Reduction in performance for milk-based beverages ~45%	o ✓ o	o o o	o o o	o o x	o o o	o o o	o o o	o o o
Grounds chute	o	o	o	o	o	o	o	o
Lockable containers (bean, powder, flavour tray, refrigerator, grounds drawer)	o	o	o	o	o	o	o	o
Payment system connection	o	o	o	o	o	o	o	o
Single outlet*	o	o	o	o	o	o	o	o
Special colours (acc. to RAL code)	o	o	o	o	o	o	o	o
Tank operation (water level monitoring kit)*	o	o	o	o	o	o	o	o
ThermoplanConnect telemetry system	o	o	o	o	o	o	o	o
Unavailable								
Foot skirting 77 mm	x	x	x	x	x	x	x	x